



lineScale 3

PPE Certified (CE and UIAA)
 Electronic Bluetooth Load Cell

Quick Start Guide

QSG ver. 2.0

This quick guide will get you started with the basic, most frequent operating functions.
Please refer to the overleaf instructions for MENU operation and available setup options.
You will find downloads, certificates, manuals, and a knowledge-base on www.linegrip.com/LS3



Long press to switch on / off.

Short press (when powered on) to enter the settings and configuration menu.

- Log settings
- Date & Time settings
- User settings
- Service Menu (Operate carefully in this menu! Wrong settings can render the LS3 inoperative!)



Short press to toggle the scan rate.

- 10Hz (100ms)
- 40Hz (25ms)
- 640Hz (1.5ms)
- 1280Hz (0,75ms)

Note: BT connection to smartphone app is possible with 10Hz and 40Hz setting only.

Long press to start onboard logging with the settings defined in the Log-Menu.

In the „User Settings“ you may activate the „Auto Power Off“ function, which is disabled by default. This will power off the LS3 automatically after a specified amount of time has passed since the last button press or load change was registered. The „Power save & lock“ function is set to 5 minutes by default because it will not affect or interrupt onboard logging or BT connection. When the display is „locked“ the LS3 will run about 4 times longer on a single battery charge. When the „lock symbol“ or „lock screen“ is displayed you can unlock the device by pressing the PWR & ZERO buttons simultaneously. With the same button combination you may manually lock the device anytime on the main screen (even while logging is active and running) to save power. Please refer to the online knowledge base or the downloadable PDF user manual for detailed operating instructions and LOG function explanation.



Short press to toggle display units.

- kN (kilonewton)
- lbf (pounds force)
- kgf (kilograms force)

Long press to toggle PEAK mode.

The load display will freeze the highest value reached since the PEAK mode was activated.



Short press to set relative zero (in REL), reset MAX/MIN (in ABS), reset PEAK.

Long press to toggle REL(ative) / ABS(olute) mode. REL mode will show load value relative to the current set relative zero.

ABS mode will always show the true / real load value relative to the calibrated absolute zero.

NOTICE FOR PPE APPLICATION

Please fully read and understand the included PPE manual before using the LineScale-3 for PPE application!

Technical Specifications

- Working load limit (WLL): 30 kN (6700 lbf)
- Minimum breaking strength (MBS): 90 kN (22000 lbf)
- Recommended PPE max. load: 10 kN (2200 lbf)
- Max. measuring range: -10 % to 110 % of WLL
- Sensor scan rate (cycle rate): 1280Hz, 640Hz, 40 Hz, 10Hz
- Weight (incl. battery): 520 g (18.3 oz)
- Measurements (L x W x T): 190 x 90 x 20 mm
- Material body: High strain aviation aluminum alloy LY12CZ
- Display units: kN / kgf / lbf
- Display division (resolution): 0.01 kN / 1 kg / 2 lbf
- Measure error: less than ±0.5% (@3kN-15kN)
- Operating temperature: -10 to +40 °C
- Storage temperature: -20 to +70 °C
- Relative humidity: 10% to 80% RH
- Power: 3.7V 1600mAh rechargeable Li-Ion battery pack
- Operating endurance: ca. 50 hours continuous (24h w. bluetooth enabled)
- Bluetooth 4/5 interface (w. smartphone app)
- Protection Class: IP66 (splash & rain proof, **do NOT submerge in water!!!**)



Your devices Bluetooth MAC-Address is engraved above the display. This is used for unit identification in the smartphone app when multiple units are in Bluetooth reach, and it is also the serial number of your unit.

lineGrip Corporation Ltd.

Hauptstrasse 41
 67714 Waldfischbach
 Germany

Contact: Mr. Andy Riedrich
 Phone: +49 6333 603 00 22
 Mobile: +49 170 996 91 92

info@linegrip.com
 www.linegrip.com

Scan QR-code to download users manual, apps, firmware, certificates, and access FAQs.



When in Main-Menu, the top most row will display the date, firmware version, and time.

30.12.21

V2.520

16:45

Main Menu

Sub Menu

Item

(w. sample setting)

(possible settings)

Log	Sub Menu	Item
	Clear log memory NO	Sure delete all logs? NO YES
	Onboard logging ON	Onboard logging ON OFF
	Overwrite oldest log ON	Overwrite oldest log ON OFF
	Capture start trigger 1.00 kN	Set start trigger x.xxx 00000 for none
	Capture end trigger 12.00 kN	Set end trigger x.xxx 00000 for none
	Scan rate 40 Hz	Set scan rate 10 Hz, 40 Hz, 640 Hz, 1280 Hz
	Max log rec time 180 sec.	Set max log rec time xxxxx
	Min log rec time 10 sec.	Set min log rec time xxxxx
	Pre-capture rec time 5 sec.	Set pre-capture time xxxxx 00000 for none
	Logging type Continuous logging	Set logging type Continuous logging Single log
	Return	
Date/Time	Date format	Date format dd.mm.yy yy/mm/dd
	Date 01.10.21	Set date dd.mm.yy or yy/mm/dd
	Time 16:45:00	Set time hh:mm:ss
	Return	
User Settings	Auto power off 5 min.	Set auto power off Off, 1, 3, 5, 10, 20, 30, 60
	Power save & lock 300 sec.	Set power save & lock Off, 10, 30, 60, 100, 200, 300, 600
	Power save lock level Max power save	Power save lock level Min power save Medium power save Max power save
	Auto zero tracking 1 div.	Set zero tracking Off, 0.5, 1, 2, 3, 5, 10
	Return	
Service	Reset abs zero	Reset abs zero now? NO YES
	Set absolute zero	Cal. abs. zero now? NO YES
	Simple calibration	Start simple cal now? NO YES
	Linear calibration	Start linear cal now? NO YES
	Calibrate accel. 9.792 NiKg	Set cal. accel. x.xxxxx
	User acceleration 9.807 NiKg	Set user accel. x.xxx
	Battery voltage 3.985 V	No setting, value for information only.
	AD internal code 3513	No setting, value for information only.
	Bluetooth MAC addr. F0:F8:F2:6A:D1:8D	No setting, value for information only.
	Factory reset	Factory reset will delete ALL memory and reset all log + user values! Sure to continue? NO YES
	Return	
Exit		

Buttons function for navigation and setting

When enter item, NO is highlighted, press **↔** to return without deleting. Select **▼** YES and press **↔** to clear log memory and return to Sub-Menu

When enter item, current setting is highlighted
Select **▲▼** ON or OFF
press **↔** to set and return to Sub-Menu

When enter item, current setting is highlighted
Select **▲▼** ON or OFF
press **↔** to set and return to Sub-Menu

When enter item the current set value is **edited per digit**

press **↔** to set value
first digit is highlighted
change digit with **▲▼** and **↔** to set
next digit is highlighted
change digit with **▲▼** and **↔** to set
repeat same for all digits
on last digit
press **↔** to set value and return to Sub-Menu

Enter all zeroes (00000) for no triggers or recording
press **↔** to set and return to Sub-Menu
press PWR to abort edit and return to Sub-Menu

When enter Scan Rate, current setting is highlighted
Select **▲▼** 10, 40, 640, 1280Hz
press **↔** to set and return to Sub-Menu

Max Log Rec, Min. Log Rec, Pre-Capture will show the
distinct time sections for the respective selected Scan Rate.
When enter item, current setting is highlighted
Select **▲▼** Continuous or Single
press **↔** to set and return to Sub-Menu

Press **↔** to exit Sub-Menu, and return to Main-Menu

When enter item, current setting is highlighted
Select **▲▼** to toggle date format
press **↔** to set and return to Sub-Menu

Same button function as "edited per digit" above

Same button function as "edited per digit" above

Press **↔** to exit Sub-Menu, and return to Main-Menu

When enter item, current setting is highlighted
Select **▲▼** to toggle Minutes for Power Off
press **↔** to set and return to Sub-Menu

When enter item, current setting is highlighted
Select **▲▼** to toggle Seconds for Power Save & Lock
press **↔** to set and return to Sub-Menu

When enter item, current setting is highlighted
Select **▲▼** Min, Medium or Max for Power Save Level
press **↔** to set and return to Sub-Menu

Same button function as select value

Press **↔** to exit Sub-Menu, and return to Main-Menu

When enter item, NO is highlighted, press **↔** to return
Select **▼** YES
press **↔** to cal abs. 0 and return to Sub-Menu

When enter item, NO is highlighted, press **↔** to return
Select **▼** YES
press **↔** to cal abs. 0 and return to Sub-Menu

When enter item, NO is highlighted, press **↔** to return
Select **▼** YES
press **↔** to start simple 2-point calibration

When enter item, NO is highlighted, press **↔** to return
Select **▼** YES
press **↔** to start linear 3-point calibration

Same button function as "edited per digit" above

Same button function as "edited per digit" above

Menu operation tip:

Press the PWR button at any time during item setting to abort the setting operation, and return to the Sub-Menu without saving any changes to the current item ;-)

From Sub-Menu press PWR to return to Main, from Main-Menu press PWR to exit Menu.

When enter item, NO is highlighted, press **↔** to return
Select **▼** YES
press **↔** to reset the LS3 to factory defaults & erase memory.
NOTE: this will NOT reset the calibration values!!!

Press **↔** to exit Sub-Menu, and return to Main-Menu

Press **↔** to exit menu, and return to display screen